



Hot Water Economy

CONDENSATE REMOVAL PUMP

The Hot Water Economy pump ensures efficient, quiet operation at high temperatures, handling demanding applications with ease. Built to withstand water temperatures up to 100°C, it's ideal for industrial and commercial air handling units.




900L/h max. flow



6m max. rec. head
(flow rate 280L/h)



5.2 kg



Key Features

- High performance
- Handles 100°C water
- High level safety switch
- 40mm inlet


Suitability

- Up to 1200kW / 4m Btu/h
- Humidifiers; refrigeration; air handling units (AHUs)
- **Perfect for...** Humidifiers



HOT WATER ECONOMY @ 230 VAC 50Hz

Max. flow	900L/h
Max. rec. head	6m
Tank capacity	4L
Sound level@1m	64dB(A)
Power supply	230 VAC 50Hz 1.1A
Rated	Continuous
Class	I appliance
Max. ambient temp	40°C / 104°F
Max. water temp	100°C / 212°F
Inlet/outlet	40mm in, 10mm out
IP Protection	IP20
Safety switch	5.0A Normally closed



SUGGESTED XTRA ACCESSORIES

Description	Part No.
Rubber Adaptor 3/4" (19mm) – 1 1/2" (38mm)	FP2007
Tube To Soil Stack Adaptor	FP2038
Vinyl Tube Braided 3/8" (10mm)	AX5111



For more installation accessories take a look at our Aspen Xtra range

HOT WATER ECONOMY OPTIONS

Hot Water Economy FP2092/3

IN THE BOX

Hot Water Economy Pump • Hard wired 2m power cable • Install manual

Download manual at aspenspumps.com